



ALURAMICA

DESCRIPTION

Aluminium plate with ceramic surface treatment. Thicknesses can be obtained according to needs between 5 to 50 microns.

TECHNOLOGY

- Our Technology is absolutely ecological, without any type of aggressiveness for people or the environment.
- It does not bring about toxic or aggressive gas emanation or substances for the surroundings during the surface treatment.
- The electrolyte is non-inflammable, non-irritating, non-toxic, non-acid...etc.
- The ceramic process does not bring residues to eliminate.

CHARACTERISTICS

- Insulator of cold and heat.
- Dielectric.
- Absolute solution protection of any environmental aggressiveness.
- Excellent behaviour like promoter of anchorage for after-treatments like printing, lacquering, etc.
- High corrosion resistance, up to 3000 hours in saline fog.

RECOMMENDED APLICATIONS

- For digital and screen printing.
- For outdoor decoration.
- Printed or lacquered outdoor shells for furniture, doors, lamps, etc.
- For the aeronautic, automotive and nautical sector.
- In the field of the manufacture of electrical and/or electronic components.

ADDITIONAL INFORMATION

www.kopimask.com

Safety data sheet is available through Kopimask or your nearer supplier.

KOPIMASK, S.A. Tlph. 00 34 93 863 93 50 Fax 00 34 93 864 70 37 e-mail kopimask@kopimask.es

The data here contained is the more accurate as possible, based on our present knowledge. Nevertheless, no guarantee regarding its reliability can be given as we cannot anticipate every possible application. For the same reason our products are sold without guarantee and under the condition that users will make their own tests in order to value if the product satisfies their necessities. KOPIMASK, S.A. reserves its rights to make any modifications without previous warning.



ISO9001:2000