

DISOLIX 50

Screen conditioner

DESCRIPTION

Screen cleaner solvent for all kinds of screen printing inks.

RECOMMENDED APPLICATION

Automatic system	According to the manufacturer instructions.
Manual system	Yes.
Water based inks	Yes.
Solvent based inks: vinyl and two components	Yes.
Solvent based inks: commons	Yes.
UV water based inks	Yes.
UV solvent based inks	Yes.
Two components inks	Yes.

CHARACTERISTICS

Colour	Colourless.
Solubility in water	Yes.
Flash point	Upper 45°C

PACKAGING

20 L. drum	1 unit x 20 L.
60 L. drum	1 unit x 60 L.

SAFETY CONDITIONS

Easily flammable product. Use in well-ventilated area. See SAFETY DATA SHEET

INSTRUCTIONS OF USE

Apply over both sides of the screen with a sponge, brush, rag,... let the product acts during some minutes (depending on the screen condition).

ADDITIONAL INFORMATION

Safety data sheet is available through Kopimask or your nearer supplier.

KOPIMASK, S.A. Tlph. 00 34 93 863 93 50 Fax 00 34 93 864 70 37 e-mail kopimask@kopimask.es

The data here contained is the more accurate as possible, based on our present knowledge. Nevertheless, no guarantee regarding its reliability can be given as we cannot anticipate every possible application. For the same reason our products are sold without guarantee and under the condition that users will make their own tests in order to value if the product satisfies their necessities. KOPIMASK, S.A. reserves its rights to make any modifications without previous warning.



ISO 9001:2000 Nº : E204216



www.kopimask.com