

FIJADOR FIX S-15

Photographic Fixer

DESCRIPTION

Concentrated fluid fixer mostly suitable for Lith, Line or Contone film processing in middle or deep tank machine. It is also suitable for using in a bucket. It is used either as loading solution or regenerator.

RECOMMENDED APPLICATION

Automatic processes	Yes
Manuel processes	Yes

CHARACTERISTICS

Color	Colorless
pH	4,8 - 5

PACKAGING

20 Liters box	4 units of 5 liters
---------------	---------------------

INSTRUCTIONS OF USE

- For each 5 liters of FIXER FIX S-15 you must add a proportion of 20 liters of water, obtaining 25 liters of developer.

ADDITIONAL INFORMATION

Safety data sheet is available through Kopimask or your nearer supplier.
KOPIMASK, S.A. Tlph. 00 34 93 863 93 50 Fax 00 34 93 864 70 37 e-mail kopimask@kopimask.es

The data here contained is the more accurate as possible, based on our present knowledge. Nevertheless, no guarantee regarding its reliability can be given as we cannot anticipate every possible application. For the same reason our products are sold without guarantee and under the condition that users will make their own tests in order to value if the product satisfies their necessities. KOPIMASK, S.A. reserves its rights to make any modifications without previous warning.



ISO 9001:2000 N° : E204216

www.kopimask.com