

**FIXAPLAST**

Chemical catalyser

**DESCRIPTION**

Universal hardener for catalysed/hardened emulsions, resistance to aqueous inks.

**CHARACTERISTICS**

Physical Form	Liquid.
Colour	Pink.
Irritating	Yes.
Solubility in water	Miscible

**PACKAGING**

20 L box	4 units x 5 L
----------	---------------

**SAFETY CONDITIONS**

Irritating product. Use gloves and goggles. See SAFETY DATA SHEET.

**INSTRUCTIONS OF USE****Post Hardening / Chemically**

Once the screen is exposed and completely dried, apply **FIXAPLAST** on both faces with a sponge, and leave the screen dry in a horizontal position under a temperature of 40°C, during 1 - 2 hours. It could also be hardened under environmental temperature ( 18 – 22 °C ) within 24 hours. (from today to another day).

**ADDITIONAL INFORMATION**

Safety data sheet is available through Kopimask or your nearer supplier.  
KOPIMASK, S.A. Tlph. 00 34 93 863 93 50 Fax 00 34 93 864 70 37 e-mail kopimask@kopimask.es

The data here contained is the more accurate as possible, based on our present knowledge. Nevertheless, no guarantee regarding its reliability can be given as we cannot anticipate every possible application. For the same reason our products are sold without guarantee and under the condition that users will make their own tests in order to value if the product satisfies their necessities. KOPIMASK, S.A. reserves its rights to make any modifications without previous warning.



ISO 9001:2000 N°: E204216

[www.kopimask.com](http://www.kopimask.com)