

GEL FARLUX

Anti-set-off conditioner

DESCRIPTION

Anti-set-off for offset inks formulated for make smoother the ink into the battery and dry it in the sheet by tixotropic action.

With **GEL FARLUX** you will obtain a better drying, avoiding the re painting in more than 80%, reducing or eliminating antimaculate powder, saving until a 10% of ink, less stopping of machines by accumulation of ink in the rubber, better control of the balance water/ink and specially in high speeds, colours more intense and greater brightness.

APLICATIONS SPECIALLY RECOMMENDED

- Under-printing.
- Printing in metallic inks.
- Printing in art printing paper.
- Printing in recycled papers.
- Printing in vegetal papers.
- Printing in paper board.

CHARACTERISTICS

Colour	White
Physical form	Paste
Inflammable	No

PACKAGING

Box of 12 Kg.	12 units of 1 Kg.
---------------	-------------------

INSTRUCTIONS OF USE

Add between 2% and 3% of **GEL FARLUX** into the ink (20 – 30 gr./Kg.) Its not recommended to exceed the 4%.

Shake/mix until the total incorporation with the ink.

ADDITIONAL INFORMATION

Safety data sheet is available through Kopimask or your nearer supplier.

KOPIMASK, S.A. Telf. 00 34 93 863 93 50 Fax 00 34 93 864 70 37 e-mail: kopimask@kopimask.es

The data here contained is the more accurate as possible, based on our present knowledge. Nevertheless, no guarantee regarding its reliability can be given as we cannot anticipate every possible application. For the same reason our products are sold without guarantee and under the condition that users will make their own test in order to value if the product satisfies their necessities. KOPIMASK, S.A. reserves its rights to make any modifications without previous warning.



ISO9001:2000 N°: E204216



www.kopimask.com