

KOPI-GLASMAT PASTE N°1

Glass engraving-matting paste

DESCRIPTION

Special Product for Screen Printing. Engraving–matting special paste suitable for Screen Printing application in every type of glass (except for borosilicate) . By using it, a fast engraving design or matt looking image can be obtained in only some minutes which keeps permanently. Is also effective on glazed ceramic surfaces.

APPLICATION AREA

Matting glass
 Engraving letters, logos, etc. on glass surfaces
 Decoration on glass and mirrors
 Screen Printing on glazed ceramic surfaces

CHARACTERISTICS

Colour	Pink.
Corrosive	Yes.

PACKAGING

Box 12 Kg.	12 units of 1 Kg.
Box 24 Kg.	4 units of 6 Kg.

SAFETY CONDITIONS

Corrosive product. Use gloves, safety glasses... See SAFETY DATA SHEET.

INSTRUCTIONS OF USE

Prepare the KOPI-GLASMAT for printing, according to the desired texture pure or adding up to 1 part of KOPI-GLASMAT Thinner per 5 parts of KOPI-GLASMAT Paste. Stir it using only plastic or wooden utensil, because KOPI-GLASMAT rusts most of the metals.

Bear in mind that this product must be at a temperature between 23°C to 26°C. In case of having been exposed to low temperatures, crystals might have been formed, these will disappear warming the pots in water bath to 25°C -30 °C.

We advise to work with a polyester fabric of 34 to 49 per cm mesh (86 to 123 per inch mesh) and a water-resistant emulsions, like our emulsions ROTOMASK CS, ROTOMASK-S, ROTO POLYMER HR or ZOICO COAT-WR.

The glass must be clean and degreased, dry and at ambient temperature, before the printing process starts.

It is recommended to use a soft squeegee blade, 60° shore hardness.

Use the paste like a ink, to get a good cover on the glass, a sharp-flood-coat is necessary before the print. After printing wait 3-5 minutes for KOPI-GLASMAT reaction on the glass. Clean the glass with abundant water. Good ventilation in the working place is advisable.

Screens should be cleaned with water immediately after used, for KOPI-GLASMAT may close the mesh if it dry. All leads and devices should be carefully cleaned after the printing is finished.

KOPI-GLASMAT PASTE N°1

Glass engraving-matting paste

ADDITIONAL INFORMATION

You can obtain the safety data sheet by requesting it from Kopimask or on your nearest supplier
KOPIMASK, S.A. Telf. 00 34 93 863 93 50 Fax 00 34 93 864 70 37 e-mail kopimask@kopimask.es

The facilitates dates to our present knowledge are the most precise. We can't give any guarantee on its reliability, we can't advance every possible application. We send our products without guarantee and with the condition that the users do their own test if the product satisfies their necessities. KOPIMASK, S.A. has the right to implement any modification considered to be useful, without any previous notice.



ISO 9001:2000 N°: E204216

www.kopimask.com